

High Speed Glue Spraying Machine

Equipment Specification					Standard configuration	Selection
Name of equipment	Automatic glue spray machine	Gas Source	Purity	No oil/water/impurity	CCD visual location	Automatic nozzle cleaner
Type of equipment	XLB-Q650		Air pressure	0.7-0.8 kpa	High-speed jet valve	Pressure Maintenance System
Spray speed	45000PCS/H	Exterior dimensions	Length	200 mm	Automatic loading and unloading	The scope of dispensing can be customized
Maximum speed	800 mm/s (X, Y)		Width	100 mm	High strength fuselage	Power outage emergency system
Positioning accuracy	±0.01 mm		High	150 mm	Import of Main Parts	Low level detection and alarm
Repetition accuracy	±0.01 mm	Scope of dispensing	Length	550 mm	Sound and light alarm	Laser altimetry
Input Power	50HZ AC220		Width	400 mm	Spray heating	
Ambient temperature	5-40 C	Operating system	Windows7		Track automatically widened narrow	
Environmental humidity	20-90%	Weight	580 (KG)			

Product Features:

- 1 Glue spray speed industry leading ,45000 points / H;
- 2 CCD visual positioning system. Sweep MAKE point line work, can effectively solve the plate position problem;
- 3 Full series of imported servo motor + ball screw drive, accurate position;
- 4 Using trigger flight dispensing technology;
- 5 Computer control, Windows operating system, fault acousto-optic alarm and menu display;
- 6 High speed non-contact dispensing;
- 7 Automatic thermostatic system of valve body to ensure the same effect of dispensing

molding;

8 Optional type of glue valve, optional laser altimetry;

Photo Ref.:

