

No	Description
1	MR20 Off-Line Radial Insertion Machine  - Component Stations:20 pcs - Lead Span type : 2.5/5.0/7.5mm - Component Height: Max 23mm - Component Diameter: Max 13mm - Board Size: Min 50mm*50mm,Max 400mm*300mm - Theoretical Speed: approx 20000cph - Insertion Direction: +90~-90°, 1° increment - Board Thickness: 0.79~2.36mm - In Load Board Height:900±20mm - Track Width: 50mm~300mm (adjustable) - Cut & Clinch Length: 1.2/1.5/1.8 mm (option) - Clinch Angle: 25~45°external bending - Machine Dimension: L1900xD1500xH1700 mm - Component Station Size: 1800mm×1450mm×1100mm - Weight: approx 1500KG - Power Requirement:220V , AC,50/60HZ,1.5KW - Air Pressure:0.6MPA - Air Consumption: 0.3 M3/min - Environmental Temperature:5-25° - Hole Position Correction Mode: Machine Vision System, Multiple Position Point Correction - Axis Driving System: AC Servo AC Motor - Data Input Style: USB Interface Input (Excel Format) - Control System: Chinese/English Interface (Windows Platform) - Operation Mode: Auto/Semi Auto/Manual - Workable Rotation:Conveyor Track - Board In Load: Right to Left (option) - Programming: On-line manual programming